

STUCCO ANTICO

Technical Detail Sheet

GENERAL DESCRIPTION

Stucco Antico stands out as a top-notch water-based putty that has been meticulously crafted using a blend of emulsion resins, special oils, and common mineral limes. This carefully formulated composition gives rise to an extraordinary marble-like finish effect when applied to interior surfaces. The glossy appearance achieved with Stucco Antico not only imparts a luxurious touch to the decor but also showcases captivating subtle shade variations, further enhancing its visual appeal. The marble-like finish effect adds an air of sophistication and elegance to any space, instantly transforming it into a captivating visual masterpiece. Whether it is used in residential or commercial settings, Stucco Antico elevates the ambiance, creating an atmosphere that exudes beauty and refinement.

CHARACTERISTICS AND PHYSICAL PROPERTIES

| | |
|-------------------------|--|
| Appearance | Glossy with Matt Shade |
| Density | 1.85 kg/L |
| Volume | 54% |
| Coverage | 12 months |
| Specific Gravity | 1.0-1.5 kg/sqm on plaster 0.4-6.0 kg/sqm on gypsum |
| Average Coats | 2 or more |
| Drying Time | 4-6 hours |
| Recoating | After 6 hours |
| Dilution | Ready to use |
| VOC | 35 gms/L |

MAJOR USES

Stucco Antico is specifically designed for enhancing interior plasters and gypsum surfaces. This water-soluble material not only ensures ease of application but also prioritizes environmental safety. With its smooth texture and touch, this coating offers a delightful tactile experience. Furthermore, it is completely odorless and non-toxic, ensuring a healthy and safe environment for occupants. The visual appeal of this coating is truly remarkable, as it adds an aesthetically pleasing touch to any interior space.

METHODS OF APPLICATION

- To prepare highly absorbent and chalky surfaces, it is advisable to apply MAS Masonry Primer or Primart as an initial coating. Smooth out any flaws by using MAS PVA Wall Filler to ensure a flawless base. Finally, seal the surface with Mascryl Matt Emulsion, preferably in a color that closely matches the desired Stucco shade.
- To achieve a consistent appearance, utilize a stainless steel spatula to apply MAS Stucco and create a smooth, even surface.
- Wait for a period of 6 hours after the application of the final coat, and then use sandpaper to eliminate surface imperfections and achieve a smoother finish.
- Using a stainless steel spatula, carefully and comprehensively apply the final layer of marble stucco. For a varied effect, experiment with spatulas of different sizes and apply the stucco in an artistic manner.

- After a period of 5 to 10 minutes, exert pressure on the spatula and glide it across the surface to achieve heightened glossy effects.

STORAGE

The minimum shelf life of Stucco Antico is 12 months when stored below 25°C.

CLEANING OF TOOLS

All tools should be cleaned with water as soon as possible.

PHYSIOLOGICAL HAZARDS

Although Stucco Antico is solvent-free, it is still advisable to ensure good ventilation in the working area and to use appropriate safety tools and equipment. In case of ingestion, Stucco Antico can be harmful. If contact with the eyes or skin occurs, it is important to thoroughly wash with clean water and promptly seek medical advice.

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, as the paint is often used under conditions beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice